



SAFETY DATA SHEET
METHYL ETHYL KETONE

Page 1
Issued: 09/10/2002
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: METHYL ETHYL KETONE
CAS number: 78-93-3
EINECS number: 201-159-0
Index number: 606-002-00-3
Synonyms: BUTANONE
Use / description of product: Highly flammable or extremely flammable. Irritant.

Company name: Lindechem Ltd
29 North River Road
Great Yarmouth
Norfolk
NR30 1SH
United Kingdom
Tel: +44 (0) 1493 332 286
Fax: +44 (0) 1493 330 909
Emergency tel: +44 (0) 1493 850 808

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: METHYL ETHYL KETONE >90%

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.
Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET
METHYL ETHYL KETONE**5. FIRE-FIGHTING MEASURES**

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Occupational exposure limits**

TWA (8 hr exposure limit): 600 mg/m³ (OES)

STEL (15 min exposure limit): 899 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

SAFETY DATA SHEET
METHYL ETHYL KETONE**9. PHYSICAL AND CHEMICAL PROPERTIES**

State: Liquid
Colour: Colourless
Odour: Characteristic odour
Solubility in water: Miscible
Also soluble in: Most organic solvents.
Boiling point/range°C: 79.6
Melting point/range°C: -85.9
Flash point°C: -7
Relative density: 0.805

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.
Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: METHYL ETHYL KETONE
IPR RAT LD50 607 mg/kg
ORL MUS LD50 4050 mg/kg
ORL RAT LD50 2737 mg/kg
Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1193	ADR Class: 3
Packing group: II	Classification code: F1
Shipping name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)	
Labelling: 3	Hazard ID no: 33



SAFETY DATA SHEET
METHYL ETHYL KETONE**IMDG / IMO**

UN no: 1193	Class: 3
Packing group: II	EmS: 3-06
Marine pollutant: NO	Labelling: 3

IATA / ICAO

UN no: 1193	Class: 3
Packing group: II	Packing instructions: 305(P&CA); 307(PAO)
Labelling: 3	

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.
Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S25: Avoid contact with eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S33: Take precautionary measures against static discharges.
S39: Wear eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.