



SAFETY DATA SHEET
HYDROGEN PEROXIDE SOLUTION 35%

Page 1
Issued: 24/09/2002
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: HYDROGEN PEROXIDE SOLUTION 35%

CAS number: 7722-84-1

EINECS number: 231-765-0

Index number: 008-003-00-9

Synonyms: HYDROGEN DYOXIDE
HYDROGENPEROXIDE

Use / description of product: Corrosive.

Company name: Lindchem Ltd
29 North River Road
Great Yarmouth
Norfolk
NR30 1SH
United Kingdom
Tel: +44 (0) 1493 332 286
Fax: +44 (0) 1493 330 909
Emergency tel: +44 (0) 1493 850 808

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: HYDROGEN PEROXIDE SOLUTION 35% 30-50%

3. HAZARDS IDENTIFICATION

Main hazards: Contact with combustible material may cause fire. Causes burns.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If

[cont...]

SAFETY DATA SHEET
HYDROGEN PEROXIDE SOLUTION 35%

unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: Oxidising. Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Smoking is forbidden. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

TWA (8 hr exposure limit): 1.4 mg/m³ (OES)

STEL (15 min exposure limit): 2.8 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Colourless
Odour: Pungent
Oxidising: Oxidising (by EC criteria)
Boiling point/range°C: 108
Melting point/range°C: -33
Relative density: 1.132

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2014
Packing group: II
Shipping name: HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Labelling: 5.1+8

ADR Class: 5.1
Classification code: OC1
Hazard ID no: 58

**IMDG / IMO**

UN no: 2014
Packing group: II

Class: 5.1
EmS: 5.1-02

SAFETY DATA SHEET
HYDROGEN PEROXIDE SOLUTION 35%

Marine pollutant: NO**Labelling:** 5.1+8**IATA / ICAO****UN no:** 2014**Class:** 5.1**Packing group:** II**Subsidiary risk:** 8**Packing instructions:** 501(P&CA); 506(PAO)**Labelling:** 5.1+8**15. REGULATORY INFORMATION****Hazard symbols:** Oxidising.
Corrosive.**Risk phrases:** R8: Contact with combustible material may cause fire.

R34: Causes burns.

Safety phrases: S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.